


MOLYDUVAL Contactin AG



+70°C



-30°C

Contact Grease

MOLYDUVAL Contactin AG is a metallic contact grease for increasing the efficiency of electric contacts. MOLYDUVAL Contactin AG contains special synthetic fluids guaranteeing lubrication and best corrosion protection as well as microfine silver plated powder guaranteeing a good conduction.

Properties

- prevents spark erosion and burning residues at contacts
- preserves contacts
- protects against corrosion
- length life of contacts
- reduces contact crossing seizure
- free of acids
- water resistant
- does not pull dirt or dust
- low noise

Functional Range

- for lubrication of electric powered contacts at low and high voltages
- for lubrication of contacts in precision engineering
- for electric contacts of any other kind, prevents spark erosion and burning
- increases efficiency of engines and generators
- reduces friction on sliding contacts of all kind

How To Use

Clean contact areas. Apply thin.

TECHNICAL DATA	Specifications	Dimension	
Color			silver-copper
Density, 15°C	SEB181301	kg/m ³	870
Temperature Range		°C	-30 bis +70
Particle Size		µm	40-45

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδϵ

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.