


MOLYDUVAL Contactin AL



+200°C



-30°C

Contact Grease

MOLYDUVAL Contactin AL is a metallic contact grease for increasing the efficiency of electric contacts. MOLYDUVAL Contactin AL contains special synthetic fluids guaranteeing lubrication and best corrosion protection as well as microfine aluminium powder guaranteeing a good conduction.

Properties

- prevents all kind of spark erosion and burning residues at contacts
- preserves contacts and protects against corrosion, even at humidity or at heat
- length life of contacts
- reduces contact crossing seizure
- oxidation stable
- free of acids
- water resistant
- does not pull dirt or dust
- low noise

Functional Range

- for lubrication of electric powered contacts at low and high voltages
- for lubrication of contacts in precision engineering
- for electric contacts of any other kind, prevents spark erosion and burning
- reduces friction of contacts up to 30%
- increases efficiency of engines and generators
- reduces friction on sliding contacts of all kind

How To Use

Clean contact areas. Apply thin.

TECHNICAL DATA	Specifications	Dimension	
Name	DIN 51502		MLF2N-30
Color			silver
Density, 15°C	SEB181301	kg/m ³	980
Penetration	DIN 51804	0,1-mm	265-295
Temperature Range		°C	-30 bis +200
Particle Size		µm	13
Test			
Water Resistance	DIN 51807	Grade	0-90
Corrosion Protection	DIN 51802	Grade	0

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδε

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.