




MOLYDUVAL

Prometheus L 00



Long Time EP-Gear Grease

MOLYDUVAL Prometheus L 00 is a high duty lubrication grease for high loaded gears, bearings, and chains. Besides a good temperature stability it guarantees excellent wear protection and good lubrication for a long-life time.

MOLYDUVAL Prometheus L 00 is suitable for all kind of gears, bearings, slideways and sliding surfaces.

Characteristics

- excellent wear protection, high load carrying properties
- appropriate ageing- and oxidation stability
- seal compatible
- reduces friction coefficient
- protects against rust and friction corrosion

Applications

- for gears and bearings as a long time lubricant

| TECHNICAL DATAS | Specification | Unit | |
|-----------------------------|---------------|--------|--------------|
| Name | DIN 51502 | | GLPSHC00-40 |
| Base Fluid | | | Mineral Oil |
| Color | | | Yellow |
| Density, 15°C | SEB 181301 | kg/m³ | 910 |
| Worked Penetration | DIN ISO 2137 | 0,1-mm | 400-430 |
| Ruhpenetration | DIN ISO 2137 | 0,1-mm | 400-430 |
| Classification NLGI | DIN 51818 | - | 00 |
| Dropping Point | DIN ISO 2176 | °C | 180 |
| Operating Temperature Range | | °C | -30 bis +120 |

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδε

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.