

# MOLYDUVAL

## Tantalus CLP 5



### Heavy Duty Spindle Oil

MOLYDUVAL Tantalus CLP 5 is a low viscous, heavy duty multi purpose lubrication oil for high speed spindles and bearings.

MOLYDUVAL Tantalus CLP 5 is high EP treated and manufactured of high refined base oils with special cleared additives.

#### Characteristics

- reduces wear
- rust and corrosion preventive
- good high and low temperature characteristics
- high load carrying properties
- stable viscosity even under extreme working conditions
- appropriate oxidation stability

#### Applications

- as spindle oil
- as bearing fluid for high speed bearings or precision engineering bearings

#### How To Use

Apply by brush, pencil, rag, oil can, automatic lubrication system or dip lubrication.

TECHNICAL DATAS	Specifications	Unit	
Base Oil			Mineral
Density, 15°C	ISO 3675	kg/m <sup>3</sup>	870
Viscosity class	DIN 51519	ISO-VG	5
Viscosity, 40°C	DIN 51562	mm <sup>2</sup> /s	5
Flashpoint	ISO 2592	°C	132

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδε

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.