


MOLYDUVAL Zink G Spray

Glossy Zinc Protection



MOLYDUVAL Zink G Spray is a glossy long-range protection against corrosion. It contains purest metallic zinc powder for corrosion protection of all metals. Proofed according DIN 50976. Defects (micro/macro pores, cracks, scratches) will be cathodically protected.

Characteristics

- 97% zinc content
- dries quickly
- high resistance to salt and water
- Adheres reliably to all metals
- may be painted over
- very economical
- temperature resistant up to + 500°C
- FCKW - free

Applications

- for the repair of defaults in galvanized metals
- for long-time corrosion protection
- corrosion protection on temperature treated parts like exhausts, heaters a.s.o.

How To Use

Degrease and remove rust from surface. Before application shake container well for 20 seconds. Keep can 25-30 cm away from surfaces to be treated. In case several coatings shall be applied, wait 5-8 min. after each treatment.

TECHNICAL DATAS	Spec.	Unit	
Color			silver
Appearance			glossy
Packing		ml	400
Productiveness		m ² /can	4
Drying Time		min	5
Protection Time, max.		years	3-5

For more information call +49 2102 9757-28 or contact us at <http://www.molyduval.com> αβχδϵ

The technical information in this technical data sheet represents our present knowledge.

Because of complexity of tribological systems it does not form part of any sales contract as guaranteed properties of the delivered material.